



拆卸和安装霍尔传感器 3 -G300-

Hazet 6290-1 CT 	Hazet 6402-1 
Hazet 1557/32 	Hazet 854-1 
CH92-10145	

所需要的专用工具和维修设备

- ◆ 扭力扳手 (5 - 60Nm) -HAZET 6290-1CT- 或 -V.A.G 1331-
- ◆ 棘轮头 -HAZET 6402-1-
- ◆ TORX 工具 -HAZET 1557/32-
- ◆ 小型套装工具 -HAZET 854-1-
- ◆ 转换接头 (3/8 转 4/1) -HAZET 8858-2-

拆卸

- 拆卸空气滤清器壳体。 → Kapitel „拆卸和安装空气滤清器壳体；All New Lavida 2018；All New Gran Lavida 2019；T-Cross2019；All New Polo 2019；Touran L 2019；Lavida SR 2018；Lavida SR 2019“
- 拔下电气插头连接 -1-。

- 旋出螺栓 -2-, 拉出霍尔传感器 3 -G300-。

安装

安装以拆卸的相反顺序进行。

拧紧力矩

- ♦ → Kapitel „点火装置 - 装配概览“
- ♦ → Kapitel „空气滤清器壳体 - 装配概览 ; All New Lavidia 2018 ; All New Gran Lavidia 2019 ; T-Cross2019 ; All New Polo 2019 ; Touran L 2019“

