



规格

发动机	变速器	万向节类型		最大允许角度	
		外部	内部	外部	内部
汽油 2.0	M/T	BJ#95	TJ#95	45%	21°
	A/T	BJ#95	TJ#95	45%	21°
汽油 2.4	M/T	BJ#95	TJ#95	45%	21°
	A/T	BJ#95	TJ#95	45%	21°

规定扭矩:

项目		N. m	kgf. m	lb • ft
前	车轮螺母	88.2~107.8	9.0~11.0	65.0~79.5
	传动轴槽顶螺母	196.1~274.6	20.0~28.0	144.7~202.5
	支柱总成下部装配螺栓	137.2~156.9	14.0~16.0	101.2~115.7
	制动钳装配螺栓	78.4~98.0	8.0~10.0	57.8~72.3
	轮速传感器固定螺栓	6.8~10.7	0.7~1.1	5.0~7.9
	制动盘装配螺栓	4.9~5.8	0.5~0.6	3.6~4.3
	下部球节装配螺栓	98.0~117.6	10.0~12.0	72.3~86.7
	横拉杆末端球节螺母	34.3~44.0	3.5~4.5	25.3~32.5
后	车轮螺母	88.2~107.8	9.0~11.0	65.0~79.5
	减振器上部装配螺栓	49.0~63.7	5.0~6.5	36.2~47.0
	减振器下部装配螺栓	137.2~156.9	14.0~16.0	101.2~115.7
	制动钳装配螺栓	49.0~58.8	5.0~6.0	36.2~43.4
	轮速传感器固定螺栓	6.8~10.7	0.7~1.1	5.0~7.9
	制动盘装配螺栓	4.9~5.8	0.5~0.6	3.6~4.3
	鼓总成装配螺栓	58.8~68.6	6.0~7.0	43.4~50.6
	上臂球节装配螺母	137.2~156.9	14.0~16.0	101.2~115.7
	下臂固定螺栓	137.2~156.9	14.0~16.0	101.2~115.7
	辅助臂球节装配螺母	44.1~53.9	4.5~5.5	32.5~39.7
	纵臂固定螺栓	44.1~53.9	4.5~5.5	32.5~39.7

润滑油

发动机		润滑油	数量
前驱动轴	BJ#24	RBA或RBAC	100g



2014 > G 2.4 MPI > 驱动轴和车桥 > 一般事项 > 规格

	TJ#24	CW-13TJ或9TWC	145g
--	-------	--------------	------